■ **Electrical Characteristics** (T_J=25 unless otherwise noted)

Parameter	Symbol	Conditions	Min	

Typical Electrical and Thermal Characteristics Diagrams

Figure 9. Normalized breakdown voltage 1701oy79 G6[(d)]TJETQq0.0000081582 0 5BTur.04 reW* n

■ SOT-323 Package information

DIMENSIONS		
SYMBOL	INCHES	
	MIN.	
A	0.035	
A1	0.000	
A2	0.035	
b	0.006	
c	0.004	
D	0.071	
E		
E1	0.085	

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http://www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.