

DBD'D`Ugh]W!9bWUdgi`UhY`HfUbg]ghcf



:YUhiFYg`

- Epoxy meets UL-94 V-0 flammability rating
- Moisture Sensitivity Level 1
- High power dissipation capability
- Part no. with suffix "Q" means AEC-Q101 qualified


5dd`]WUh]cb`

- Linear voltage regulators Low-side switches
- Battery-driven devices MOSFET drivers
- Amplifiers

AYW\Ub]WU`8UhU`

- DUW_U[Y: SOT-223
- HYfa]bU`g. Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Auf_]b[. BCP52-16

9ei]]U`Ybh`W]fWi]h`




CfXYf]b[`:bzcf aUh]cb` (Example)`

DF9:9F98`D#B`	D57?-B;` 7C89`	IB=H`K9=: <Hfl[L`	A=B=A A` D57?5; 9fidWgt`	=BB9F`6CL` E 5BH=HMfidWgt`	C H9F`75FHCB` E 5BH=HMfidWgt`	89@=J9FM`AC89`
BCP52-16Q	F2	Approximate 0.11	2500	5000	25000	13" reel




7 \UfUWhYf]gh]Wg (Typical)

GCH!&&' DUW_U [Y'C i h'] bY' 8] a Ybg] cbg'



GCH!&&' G i [[YghYX'DUX'@Umc i h'





6 7 D) & ! % * E

8] g W U] a Y f

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.