

YJD106506DQG2Q

Typical Applications

Typical applications are in power inverter, uninterruptible power supplies, automotive battery chargers.

Mechanical Data

- Package: TO-252
- Molding compound meets UL 94 V-0 rating, RoHS-compliant, halogen-free
- Terminals: Tin plated leads
- Polarity: As marked

Maximum Ratings (Tc=25°C Unless otherwise specified)


PARAMTETER	SYMBOL	UNIT	VALUE
Device marking code			D106506DQG2
Reverse voltage (repetitive) @ 25°C	V_{RRM}	V	650
Reverse voltage (Surge Peak) @ 25°C	V_{RSM}	V	650
Reverse voltage (DC) @ 25°C	V_{DC}	V	650
Continuous forward current @ T		A	23
Continuous forward current @ T			11

Continuous forward current @ T





Outline Dimensions



TO-252		
Dim	Min	Max
A	6.500	6.700
B	5.100	5.460
C	1.400	1.800
D	6.000	6.200
E	10.000	10.400
F	2.166	2.366
G	0.660	0.860
H	Φ1.050	Φ1.350
I	0.460	0.580
J	2.200	2.400
K	0	0.300
L	0.890	2.290
M	2.280	2.700
N	0.430	0.580
O	4.20	4.95



Disclaimer

The information in this document is for reference only. Yangzhou Yangji Technology Co., Ltd. reserves the right to make changes without notice and does not assume any responsibility for errors or omissions.

The product listed here is not intended for use in life support or safety-critical equipment or devices, or in medical instruments, or in nuclear safety control systems. Yangji Technology Co., Ltd. does not assume any responsibility for damages or losses caused by the use of the product in such applications.

This publication is for reference only. For more information, please visit the website <http://www.21yangji.com> or contact your local sales representative for further information.