



HS1A THRU HS1M

Surface Mount High Efficient Rectifier

Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super fast reverse recovery time
- Meets MSL level 1 , per J-STD-020 , LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies , inverters , converters , and freewheeling diodes for consumer , and telecommunication.

Mechanical Data

- Package: DO-214AC (SMA)
- Molding compound meets UL 94 V-0 flammability rating , RoHS-compliant , halogen-free
- Terminals: Tin plated leads , solderable per J-STD-002 and JESD22-B102
- Polarity: Cathode line denotes the cathode end

■Maximum Ratings (Ta = 25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	HS1A	HS1B	HS1D	HS1F	HS1G	HS1J	HS1K	HS1M
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	300	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	210	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	300	400	600	800	1000
Average rectified output current @60Hz sine wave , Resistance load , TL (FIG.1)	IO	A	1.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave , 1 cycle , Tj = 25°C	IFSM	A	30							
Forward Surge Current (Non-repetitive) @1ms , square wave , 1 cycle , Tj = 25°C			60							
Current squared time @1ms to 8.3ms Tj = 25°C	I²t	A²s	3.735							
Storage temperature	Tstg	°C	-55 ~ +150							
Junction temperature	Tj	°C	-55 ~ +150							

■Electrical Characteristics Ta = 25°C Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	HS1A	HS1B	HS1D	HS1F	HS1G	HS1J	HS1K	HS1M
Maximum instantaneous forward voltage	V _F	V	I _{FM} = 1.0A	1.0			1.3		1.7		
Maximum reverse recovery time	t _{rr}	ns	I _F = 0.5A, I _{RM} = 1.0A , I _{rr} = 0.25A	50					75		
Maximum DC reverse current at rated DC blocking voltage	I _R	ε A	T _j = 25	5							
			T _j = 125	100							



HS1A THRU HS1M

Thermal Characteristics^ T_a = 25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	HS1A	HS1B	HS1D	HS1F	HS1G	HS1J	HS1K	HS1M
-----------	--------	------	------	------	------	------	------	------	------	------


R_{dJ-Ah} L 9 dJ-A

Typical Thermal resistance



HS1A THRU HS1M

FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
HS1A-HS1M	F1	Approximate 0.059	5000	/	80000	13 ÷ reel
HS1A-HS1M	F2	Approximate 0.059	7 500	/	120000	13 ÷ reel
HS1A-HS1M	F3	Approximate 0.059	7 500	/	60000	13 ÷ reel
HS1A-HS1M	F4	Approximate 0.059	1800	14400	5 7 600	7 ÷ reel
HS1A-HS1M	F5	Approximate 0.059	2000	16000	64000	7 ÷ reel
HS1A-HS1M	F6	Approximate 0.059	5000	/	100000	13 ÷ reel

Outline Dimensions


DO-214AC(SMA)		
Dim	Min	Max
A	1.25	1.58
B	2.40	2.83
C	4.00	4.75
D	1.90	2.30
E	4.93	5.28
F	0.76	1.41
G	0.05	0.20
H	0.15	0.31
I	1.70	2.10

Dimensions in millio , ur u



HS1A THRU HS1M

■Suggested Pad Layout



DO-214AC(SMA)	
Dim	Millimeters
P1	4.00
P2	1.50
P3	6.50
Q1	2 . 5 0
Q 2	1 . 7 0



HS1A THRU HS1M

Disclaimer

o y c î l t l r _ f s Ä M i f b t h

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and malfunction of which would directly endanger human life (such as medical instruments, transport equipment, aerospace machinery, nuclear-reactor controls, fuel controls, and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility for any damages resulting from such improper use of sale.

This ú w _ t l n s i a p c î '

g f s o t l A d # o m Ò ' m m e a r ? x