




Surface Mount High Efficient Rectifier



Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C


Typical Applications

For use in high frequency rectification of power

¾ ct % p τ ÷ τ ¥

® ion ;

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free



- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Ta=25 Unless otherwise specified

PARAMETER	SYMBOL									
	V_{RRM}	V	50	100	200	300	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	210	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	300	400	600	800	1000
Average rectified output current @60Hz sine wave , resistance load , T_L (Fig.1)	I_O	A	2.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave , 1 cycle , $T_j = 25$	I_{FSM}	A	50							
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, $T_j=25$			100							
Current squared time @1ms≤t≤8.3ms $T_j=25$ Rating of per diode	I^2t	A ² s	10.375							
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	C_j	pF	32				17		12	
Storage temperature	T_{stg}		-55 ~ +150							
Junction temperature	T_j		-55 ~ +150							



US2A THRU US2M

■Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	US2A	US2B	US2D	US2F	US2G	US2J	US2K	US2M
Maximum instantaneous forward voltage drop per diode	V_F	V	$I_{FM}=2.0A$		1.0		1.3			1.7	



■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	
--------------	-----------------	----------------	-------------------------	--



■ Outline Dimensions

γ Suggested pad layout



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of tb