



MUR30120L

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-220AC
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (T_j=25 °C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR30120L
Repetitive Peak Reverse Voltage	V _{RRM}	V	1200
Average Rectified Output Current @60Hz half sine-wave, R-load, T _c (FIG.1)	I _O	A	30
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T _j =25 °C	I _{FSM}	A	210
Current Squared Time @1ms≤t≤8.3ms T _j =25 °C	I ² t	A ² s.	183
Single Pulse Avalanche Energy @ T _p =40us, T _j =25 °C, L=15mH	E _{AS}	mJ	2.7
Storage Temperature	T _{stg}		-55 ~ +175
Junction Temperature	T _j		-55 ~ +175
Typical Junction capacitance @4V, 1MHz		pF	97



MUR30120L

■Electrical Characteristics T_j=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V _{FM}	V	I _{FM} =30.0A T _j =25	-	2.8	3.3
			I _{FM} =30.0A T _j =125	-	2.1	2.8
DC reverse current at rated DC blocking voltage per diode	I _{RRM1}	uA	V _{RM} =V _{RRM} T _j =25	-	-	5.0
	I _{RRM2}		V _{RM} =V _{RRM} T _j =125	-	-	200
Reverse Recovery Time	T _{rr}	ns	I _F =0.5A I _{RM} =1A I _{RR} =0.25A T _j =25	-	38	70
			T _j =25	-	185	-
			T _j =125	-	272	-
Peak recovery current	I _{RRM}	A	T _j =25	-	5.4	-
			T _j =125	-	12.6	-
Reverse recovery charge	Q _{rr}	nC	T _j =25	-	509	-
			T _j =125	-	1722	-

■Thermal Characteristics T_j=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	MUR30120L
Thermal Resistance	Between junction and case	R _{θJ-C}	/W	0.98

■Ordering Information (Example)

PREFERRED P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR30120L	Approximate 1.8	50	1000	5000	Tube

■Characteristics (Typical)





FIG.5 Diagram of circuit and Testing wave form of reverse recovery time





■Outline Dimensions





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.