

Average Forward Current
@60Hz sine wave, Resistance load, Ta=65

■ $T_a=25$ Unless otherwise specified

				100		
Maximum reverse recovery time	t_{rr}	ns	$I_F=0.5A, I_R=1.0A,$ $I_{rr}=0.25A$	150	250	500

v7KHUPDO &KDUDFWHULVWLFHV RWKHUÄLVH VSHFLILHG

3\$5\$0(7(5	6<0%2	81,7	)5 *	)5 *	)5 *	)5 *	)5 *	)5 *	)5 *
7\SLFDO 7KHUPDO 5HVLVWDQFH									





v2UGHULQJ ,QIRUPDWLRQ

35()(5(' 3 1	3\$&.\$*(&2'()	81,7 : (, * + 7	0,1,080 3\$&.\$*(SFV	,11(5 %2; 48\$17,7< SF	287(5 &\$572 48\$17,7< SF	'(/,9(5< 02'()
)5 *a)5 *	'	\$SSUR[LPDWH				
)5\$ *a)5 *	&	\$SSUR[LPDWH				

7DSH
%XO

v8KDUDFWHULVWLFHV

QVWDQDQHRXV)RUZDUG 6XUJH &XUUHQW \$
\$YHUDJH)RUZDUG 2XWSXW &XUUHQW \$
\$
QVWDQDQHRXV)RUZDUG &XUUHQW \$



\$
X\$
XV





The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility.