



- High efficiency
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

: Tin plated leads, solderable per J-STD-002 and JESD22-B102

- Color band denotes cathode end

■ (Ta=25 Unless otherwise specified)

Device marking code			1N5416G
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	V	1600
Maximum RMS Voltage	V _{RMS}	V	1120
Maximum DC blocking Voltage	V _{DC}	V	1600
Average Forward Current @60Hz sine wave, Resistance load, Ta =55	I _{F(AV)}	A	3.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25	I _{FSM}	A	120
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			240
Current squared time @1ms≤t≤8.3ms Tj=25 Rating of pC≤	I ² t	A ² s	60
Typical junction capacitance @ Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	C _j	pF	27
Storage Temperature	T _{stg}		-55 ~ +150
Junction Temperature	T _j		-55 ~ +150

■ Ta=25 Unless otherwise specified

Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =3.0A	1.2
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _j =25	5
			T _j =125	150



■ Ta=25 Unless otherwise specified

--	--



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use