



Low profile package
Ideal for automated placement
Glass passivated chip junction
High forward surge capability
Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

Mechanical Date

Package: SOD-323FL

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

Polarity: Cathode line denotes the cathode end

Maximum Ratings (T_j=25 Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	FMG1A	FMG1B	FMG1D	FMG1G	FMG1J
Device marking code			1AL	1BL	1DL	1GL	1JL
Repetitive peak reverse voltage	V	V	50	100	200	400	600
Maximum RMS voltage	V _{RMS}	V	35	70	140	280	420
Average rectified output current @60Hz sine wave, resistance load, T _c =80	I _o	A	1.0				
Surge(non-repetitive)forward current @ 60Hz half-sine wave,1 cycle, T _j =25	I _{FSM}	A	20				
Current Squared Time @1ms t<8.3ms T _j =25	I ² t	A ² s	1.66				
Storage temperature	T _{STG}		-55 ~+150				
Junction temperature	T _J		-55 ~+150				

FMG1A THRU FMG1J

Electrical Characteristics $T_j=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	FMG1A	FMG1B	FMG1D	FMG1G	FMG1J
Maximum instantaneous forward voltage drop per diode	V_F	V	$I_F=1.0A$	1.1				
Typical junction capacitance	C_J	pF	$V_R=4V, 1\text{ MHz}$	4.5				
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM}	μA	$T_J=25$	5				
			$T_J=125$	50				

Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	FMG1AE	FMG1BE	FMG1DE	FMG1GE	FMG1JE
Thermal resistance	R_{J-A}	/W	270 ¹				
	R_{J-L}		85 ¹				
	R_{J-C}		60 ²				

Note:

- (1) Thermal resistance between junction and ambient and between junction and lead mounted on P.C.B without copper pad areas.
- (2) Thermal resistance between junction and cathode tab solder point.

Characteristics(Typical)

·

o
7
h

V · #



Outline Dimensions

SOD-323FL		
Dim	Min	Max
A	1.05	1.45
B	0.90	1.15
C	2.30	2.70
D	0.80	1.20
E	0.25	0.70
F	0.05	0.25

Suggested pad layout

SOD-323FL	
Dim	Millimeters
P1	



FMG1A THRU FMG1J

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.