



MBR20F60FCTS-B1-W5094HF

Schottky Diodes

" +LJK IUHTXHQF\ RSHUDWLRQ
" +LJK SXULW\ KLJK WHPSHUDWXUH HSR[\ HQ
HOKDQFHG PHFKDQF\ B-DPQW\ HQW K6 FRPSO
" Terminals 7LQ SODWHG OHDG

50 a M

Repetitive Peak Reverse Voltage	VRRM	V	60
Average Rectified Output Current @60Hz sine wave, R-load	,2	\$	
6XUJH 1RQ UHSHWLWLYH)RUZDUG &XUUHQW # +]K@LM - a			

--

0D[LPXP LQVWDQW DQHRXV IRUZDUG YROWDJH GURS SHU GLRGH	950	950	\$	
0D[LPXP '& UHYHUVH 5XUUHQW DW UDWHG '& EORFNLOJ YROWDJH SHU GLRGH	550	950 9550 7D -		
	,550	950 9550 7D -		

1RWH 3XOVH WHVW X6 SXOVH ZLGK GXW\ F\FOH
1RWH 3XOVH WHVW SXOVH ZLGK P6




MBR20F60FCTS-B1-W5094HF

Thermal Characteristics 7D



MBR20F60FCTS-B1-W5094HF

Outline Dimensions



ITO-220AB		
' L P	0 L Q	0 D [
\$		
%		
&		
'		
(		
)		
*		
+	7 < 3	
,	7 < 3	
-		
.		
/		
0		
1		
2	7 < 3	
3		
4		
5		
6	7 < 3	
7		
8		
9		



MBR20F60FCTS-B1-W5094HF

Disclaimer

7KH LQIRUPDWLRQ VSHFWXHQWQW LQ WKULUDHQHJKRXFKDRQQDZHF(KQHFWURQLF /VHG UHV
ULJKW WR PDNLHWKRXQHQWVSHFRIWVWLSURQGF FWWV GLVSPDURIGHKHUWOLDEWQWV L JXQ F
RU RWKHUZZLVH

7KH SURGXFWQLVGHV/KJHGL WR EHHXVHFWZLWQLR HGHQSDHQW RU GHYLFHWKDG Q
HTXLSPHQW RU GHYLFHV ZKLFK UHTXLWKHKEDIOXZVWOLRXDIGHGDEHFWW\ DQSDQJHU
PHGLFDO LQVWUXHQMSRWWHQWLRQHUTXLSPH H DFXKHQ U UHDFWKHU FFRQWURROOHV DQ
GHYLFHV <DQJMLHVRV DQDQH DQVXRLOV VRRWHVSRQVLEWHVROVLIQJGIDRPHVFK LP
RI VDOH

7KLV SXEOLFDWLRQ SXVSHUW DGHVLQURUPVXLSRQLSGHYLIRXVGGWLWRQDO LQWRUPDWLR
KWVZ [\DQJMLHVRV](#) FRQVXOW \RXU QHDUHVW <DQJMLHVRV DQVLEWHV RILFH IRU IXUW