





- Ideal for automated placement
- Low power losses
- H 2t2 i 2 j

† 4



- :TO-277
Molding compound meets UL 94 V-0 flammability rating,
RoHS-compliant, Halogen free
- : Tin plated leads, solderable per
J-STD-002 and JESD22-B102

(Ta=25 Unless otherwise specified)

Device marking code			SS15U45
Repetitive Peak Reverse Voltage	V_{RRM}	V	45
Average Rectified Output Current @60Hz -sine wave, R- load, Tc=65	I_O	A	15
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Ta=25	I_{FSM}	A	275

Current Squared Time @1ms≤t≤8. 1 R I M 5

Peak Forward Voltage	V_{FM}	V	$I_{FM}=15.0A, T_j=25$	-	0.43	0.47
			$I_{FM}=15.0A, T_j=125$	-	0.37	0.40
Reverse Breakdown Voltage	V_{BR}	V	$I_R=0.5mA$	45	-	-
Leakage Current	I_R	mA	$V_R=45V T_j=25$	-	-	0.5
			$V_R=45V T_j=100$	-	-	100


Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS




$T_a=25$ Unless otherwise specified

Thermal Resistance	Junction to Case	$R_{\theta J-C}$	/W	8



TO-277		
Dim	Min	Max
A	3.90	4.10
B	1.70	1.90
C	6.40	6.60
D	5.30	5.50
E	0.80	1.00
F	1.85 ref.	
G	0.35	0.45
H	1.10	1.20
I	4.10	4.50
J	1.50	1.90
K	2.90	3.40
L	0.55	0.75
M	0.50 ref.	
N	1.15 ref.	



DIM	MIN.(mm)
A	3.36
B	4.86
C	0.85
P	1.84
Q1	1.40
Q2	1.40

