


## Bridge Rectifiers

### Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.



### Mechanical Data

- **Package:** JB  
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

### ■Maximum Ratings (T<sub>a</sub>=25 °C Unless otherwise specified)

| PARAMETER                               | SYMBOL           | UNIT | D6JB05 | D6JB10 | D6JB20 | D6JB40 | D6JB60 | D6JB80 | D6JB100 |
|-----------------------------------------|------------------|------|--------|--------|--------|--------|--------|--------|---------|
| Device marking code                     |                  |      | D6JB05 | D6JB10 | D6JB20 | D6JB40 | D6JB60 | D6JB80 | D6JB100 |
| Maximum Repetitive Peak Reverse Voltage | V <sub>RRM</sub> | V    | 50     | 100    | 200    | 400    | 600    | 800    | 1000    |
| Maximum RMS Voltage                     | V <sub>RMS</sub> | V    | 35     | 70     | 140    | 280    | 420    | 560    | 700     |
| Maximum DC blocking Voltage             | V <sub>DC</sub>  | V    | 50     | 100    | 200    | 400    | 600    | 800    | 1000    |

Average Rectified Output  
Current @60Hz sine wav      Current squared time  
@1ms≤t≤8.3ms T<sub>j</sub>=25 °C, rating of per diode

|                                                         |                  |                  |            |
|---------------------------------------------------------|------------------|------------------|------------|
|                                                         | z <sub>t</sub>   | A <sup>2</sup> S | 62.5       |
| Storage temperature                                     | T <sub>stg</sub> |                  | -55 ~ +150 |
| Junction temperature                                    | T <sub>j</sub>   |                  | -55 ~ +150 |
| Dielectric strength<br>@ Terminals to case, AC 1 minute | V <sub>dis</sub> | KV               | 2          |
| Mounting torque<br>@Recommend torque 5kg cm             | Tor              | kg cm            | 8          |



### ■Electrical Characteristics    $T_a$





## D6JB05 THRU D6JB100

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.