



Bridge Rectifiers

Features

- UL recognition, file #E230084
- Universal 3-way terminals snap-on wire wrap-around or PCB mounting
- Glass passivated chip junction
- High surge current capability
- Low thermal resistance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** GBPC GBPC-W
Molding compound meets UL 94 V-0 flammability rating, RoHS-co ¹ ○ UNIT

			GBPC25005	GBPC2501	GBPC2502	GBPC2504	GBPC2506	GBPC2508	GBPC2510
Device marking code			GBPC25005	GBPC2501	GBPC2502	GBPC2504	GBPC2506	GBPC2508	GBPC2510
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	400	600	800	1000

Average rectified output current
@60Hz s

Current squared time @1ms≤t≤8.3ms Tj=25 °C, Rating of per diode	I ² t	A ² S	664
Storage temperature	Tstg		-55 ~ +150
Junction temperature	Tj		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute	Vdis	KV	2.5
Mounting torque @Recommend torque 5kg cm	Tor	kg cm	8



GBPC25005(W) THRU GBPC2510(W)

■Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GBPC25 005	GBPC2501	GBPC2502	GBPC2504	GBPC2506	GBPC2508	GBPC2510
-----------	--------	------	--------------------	---------------	----------	----------	----------	----------	----------	----------



GBPC25005(W) THRU GBPC2510(W)

A 28.2 28.8

■ Outline Dimensions

B 5831 7831

GBPC-W		
Dim	Min	Max
A	28.2	28.8
B	17.1	19.1
C	10.4	12.4
D	0.95	1.05
E	7.6	8.2
F	30	/



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.