



## Bridge Rectifiers



+



### Features

- UL recognition, file #E230084
- Universal 3-way terminals: snap-on, wire wrap-around, or PCB mounting
- Glass passivated chip junction
- High surge current capability
- Low thermal resistance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, home appliances, office equipment, industrial automation applications.

### Mechanical Data

- Package:** S25VB
- Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

### Maximum Ratings (T<sub>a</sub>=25 °C Unless otherwise specified)

PARAMETER									
Maximum Repetitive Peak Reverse Voltage	VRRM	V	100	200	400	600	800	1000	1200
Maximum RMS Voltage	VRMS	V	+0	140	280	420	560	+00	840
Maximum DC blocking Voltage	VDC	V	100	200	400	600	800	1000	1200 V
Forward Surge Current (Non-repetitive) 4 8 " 3ms ˆ Half-sine wave ˆ 1 cycle ˆ T	1 25 IFSM	A	500						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			1000						
Current squared time @1ms t 8.3ms Tj=25 , Rating of per diode	I <sup>2</sup> t	A <sup>2</sup> S	1038						
Storage temperature	Tstg		-55 ~ -55 ~ -55 ~						
Mounting torque @Recommend torque 5kg cm	Tor	kg cm	8						



# S50VB10 THRU S50VB120

## Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	S50VB10	S50VB20	S50VB40	S50VB60	S50VB80	S50VB100	S50VB120		
Maximum instantaneous forward voltage drop per diode	V <sub>F</sub>	V	I <sub>FM</sub> =25A	1.05								
Maximum DC reverse current at rated DC blocking voltage per diode	I <sub>R</sub>	μA	T <sub>j</sub> =25	5								
			T <sub>j</sub> =125	100								
Typical junction capacitance	C <sub>j</sub>	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	190								

## Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	S50VB10	S50VB20	S50VB40	S50VB60	S50VB80	S50VB100	S50VB120		
Thermal Resistance Between junction and case, With heatsink	R <sub>J-C</sub>	/W	1.0								

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

## Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT (g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S50VB10 ~ S50VB120	A1	Approximate 20	50	50	500	Paper Box

## Characteristics (Typical)

FIG1:I<sub>o</sub>-T<sub>c</sub> Curve






FIG2:Surge Forward Current Capability






# S50VB10 THRU S50VB120

FIG3: Typical Forward Voltage



## Outline Dimensions



S25VB		
Dim	Min	Max
A	31.1	32.1
B	31.1	32.1
C	17.6	18.6
D	13.7	14.7
E	15.8	16.8
F	15.8	16.8
G	0.75	0.85
H	9.5	10.5
I	/	25
J	6.2	6.4
K	4.5	5.5



## S50VB10 THRU S50VB120

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the